



ORDERING INFORMATION:

122mm STROKE: # WPA60-122  
 125mm STROKE: # WPA60-125-RIGID  
 147mm STROKE: # WPA60-147  
 150mm STROKE: # WPA60-150-RIGID  
 UNIT COMES STANDARD WITH RAP COUPLING. THE RAP COUPLING CAUSES THE STROKE TO BE .12" [3mm] LESS THAN THE NOMINAL STROKE OF THE CYLINDER. FOR HYDRAULIC CYLINDERS, ADD SUFFIX "-H". HYDRAULIC UNITS COME STANDARD WITH RIGID COUPLINGS. FOR RAP COUPLINGS, ADD SUFFIX "-RAP".

122mm STROKE: # WPA60-122-RAP-H  
 125mm STROKE: # WPA60-125-H  
 147mm STROKE: # WPA60-147-RAP-H  
 150mm STROKE: # WPA60-150-H

Rev	Date	Status	Description
3	7/9/2002	Released	END HOLE DELETED

**DO NOT SCALE DRAWING**

EXCEPT AS NOTED  
 DECIMAL TOL. SHALL BE:  
 2 PLACE ±.010  
 3 PLACE ±.005  
 4 PLACE ±.0005  
 ALL DOWEL LOCATIONS ±.0005  
 BETWEEN HOLES

<b>WEIKER</b> BEARING COMPANY		TOOL NAME WPA60 SERIES SHOTPIN - 125/150 STROKES	DATE 8/4/2001	OWNER BY RCA	ENG APPROVAL
DRAWN BY DHH	DATE 8/4/2001	OWNER BY RCA	DATE 8/4/2001	FILE NAME	SCALE 1/4

WPA60L02.DWG