



ORDERING INFORMATION:

#WPA60-{STROKE}-{COUPLER}-{DIRECTION OF STOP}
 25-100mm
 RAP or RIGID
 RET

OPTIONS NOTES:

- 1) COUPLER OPTION: RAP COUPLING CAUSES THE UNIT STROKE TO BE 3mm(.12") LESS THAN THE NOMINAL STROKE OF THE CYLINDER. UNLESS OTHERWISE SPECIFIED, THE PNEUMATIC CYLINDER COMES STANDARD WITH THE RAP COUPLING.
- 2) DIRECTION OF STOP OPTION: SPECIFY THE DIRECTION FOR THE ADJUSTABLE STOP. UNIT CAN STOP IN THE EXTEND, "-EXT", OR THE RETRACT, "-RET", DIRECTION OF STROKE. FOR DIMENSIONAL INFORMATION ON "-EXT" OPTION, SEE EXTEND STOP TEMPLATE.
- 3) UNITS COME STANDARD WITH A SHROUD AS SHOWN. TO ORDER THE UNIT WITHOUT A SHROUD, ADD SUFFIX "-NS" TO THE END OF THE PART NUMBER.

PART NUMBER EXAMPLES:

TO ORDER UNIT AS SHOWN WITH 25mm STROKE, RIGID COUPLING, & RETRACT STOP, ORDER AS:
 #WPA60-25-RIGID-RET
 TO ORDER UNIT AS SHOWN WITH A RAP COUPLING, RETRACT STOP & NO SHROUD, ORDER AS:
 #WPA60-23-NS-RET

RETRACT STOP TEMPLATE ONLY

NOTES:

1. 1.250" READ DEPTH PROX PORTS AT POSITION 1.
- THE CYLINDER CAN BE FIELD ROTATED TO PLACE THE PROX MOUNT AT ANY LOCATION.

WELKER BEARING COMPANY			
702L LINE WPA60 SERIES SHOTPIN W/ SHORT STROKE OPTION			
TEMPLATE			
DATE	DATE	CREATED BY	ENG APPROVAL
1/4/2005	02/02/03	RCA	
STATUS	SCALE	FILE NAME	
Released	1/4	WPA60L21.DWG	